



## Pressede løsflanger DIN 2642, PN 10

# INOX

Telefon: 86 89 22 11 / Fax: 86 89 29 35  
inox@inox.dk / www.inox.dk

ISO dimensioner	D	K	B	L	Bolte	C	H	4307 / 304L INOX Varenr.	4404 / 316L INOX Varenr.
DN 20 - 26,9 mm	105	75	30	13,5	4	3	14	5056060026	5056065026
DN 25 - 33,7 mm	115	85	37	13,5	4	3	14	5056060033	5056065033
DN 32 - 42,4 mm	140	100	46	17,5	4	3	15	5056060042	5056065042
DN 40 - 48,3 mm	150	110	54	18	4	4	16	5056060048	5056065048
DN 50 - 60,3 mm	165	125	65	18	4	4	18	5056060060	5056065060
DN 65 - 76,1 mm	185	145	81	18	4	4	20	5056060076	5056065076
DN 80 - 88,9 mm	200	160	94	18	8	4	20	5056060088	5056065088
DN 100 - 114,3 mm	220	180	119	18	8	4	20	5056060114	5056065114
DN 125 - 139,7 mm	250	210	145	18	8	5	21	5056060139	5056065139
DN 150 - 168,3 mm	285	240	173	22	8	5	22	5056060168	5056065168
DN 200 - 219,1 mm	340	295	225	22	8	6	26	5056060219	5056065219
DN 250 - 273,0 mm	395	350	279	22	12	6	28	5056060273	5056065273
DN 300 - 323,9 mm	445	400	329	22	12	6	31	5056060323	5056065323
DN 350 - 355,6 mm	505	460	362	22	16	8	34	5056060356	5056065356
DN 400 - 406,4 mm	565	515	413	26	16	8	36	5056060406	5056065406

DIN dimensioner	D	K	B	L	Bolte	C	H	4307 / 304L INOX Varenr.	4404 / 316L INOX Varenr.
DN 50 - 54,0 mm	165	125	58	18	4	4	18	5056060054	5056065054
DN 80 - 84,0 mm	200	160	90	18	8	4	20	5056060084	5056065084
DN 100 - 104,0 mm	220	180	110	18	8	4	21	5056060104	5056065104
DN 125 - 129,0 mm	250	210	135	18	8	5	21	5056060129	5056065129
DN 150 - 154,0 mm	285	240	160	22	8	5	22	5056060154	5056065154
DN 200 - 204,0 mm	340	295	212	22	8	6	26	5056060204	5056065204
DN 250 - 254,0 mm	395	350	262	22	12	6	28	5056060254	5056065254
DN 300 - 304,0 mm	445	400	312	22	12	6	31	5056060304	5056065304
DN 350 - 355,6 mm	505	460	362	22	16	8	34	5056060356	5056065356
DN 400 - 406,4 mm	565	515	413	26	16	8	36	5056060406	5056065406

- alle dimensioner er lagerstandard
- alle mål er i mm
- alle flanger leveres med 3.1 certifikat

